

Wall Rapture®
Mineral and metallic wallpapers
Technical data sheet – ENGLISH

Manufacturer:

Wall Rapture Germany GmbH
Hoyerswerdaer Str. 42
02625 Bautzen

Description:

The mineral & metallic Wall Rapture® wallpapers are a fleece stone or metal dispersion in different surface structures and colors.

Areas of application:

The wallpapers are only intended for indoor use. It is often used in fitness studios, hotels, shops, restaurants, conference rooms, business or representation rooms, etc., as well as in the private sector. But any objects and pieces of furniture can also be disguised.

Delivery:

Format: 300x100cm ± 1 cm *Custom-made products possible on request

Material thickness: 1.2 mm ± 0.5 mm

Weight: 0.8 kg / m² ± 0.2 kg / m² (of which 0.04 kg / m² fleece)

Bundled in a box of 1 to 5 strips

Roll weight: 2.4 kg ± 0.6 kg / m²

Package contains 750 g glue and grout per 3 m²

Shipping by shipping partners such as DHL

Items:

Standard Concrete 100 - X

Rust Concrete 140 -X

Vintage Concrete 150 - X

Structure "Lines" 170 - X

Structure "Clay" 175 - X

Standard Rust 500

X stands for the respective color that can be selected

Without number - standard light gray "typical concrete color"

5 - Anthracite

Special colors on request

The data sheet is based on development work and practical experience. The content does not indicate a contractual legal relationship. The processor / buyer is not released from the responsibility of testing our products for their suitability for the intended application. In addition, our general terms of business, delivery and payment apply. With the publication of a new edition of this data sheet, the previous information loses its validity as of 01/01/2020.

Product features:

Attention! Our products are subject to natural fluctuations during the production process. This applies in particular to slight color and structure inequalities from lane to lane. These differences are intentional and give the products a natural look without a repeat. It makes sense to lay out several strips before processing in order to be able to create an optimal overall picture.

- Look and feel: homogeneous and uneven / structured
- Breathability: open to diffusion
- Resilience: this product is normally scratch-resistant and allows liquids to be absorbed (typical of concrete) - for higher protection requirements, we refer to surface protection products
- CE classified, fire behavior according to DIN EN 13501-1: 2010-10: C-s1, d0

*available in B-s1, d0

Processing (see instructions for use):

To ensure the best possible guarantee, it is recommended that the wallpapers be glued to an even surface using the power glue provided for fleece and vinyl. Here we refer to the DIN 18365 standard neutral, non-absorbent substrate, Q3, at best Q4; if necessary, a primer must be used. The glue is ready to use and the amount is tailored to the purchased product area. Before starting construction, it is advisable to carry out a glue test on the respective substrate.

Storage:

The packaged products should ideally be stored in dry rooms at normal room temperature (at least 15 °C). For longer storage, it is advisable to unpack the sheets according to the instructions for use and to stow them in a dry place at a temperature of at least 10 °C, lying flat and covered. It must be ensured that flexibility is only given when the product body temperature reaches at least 15 °C!

Before using the Wall Rapture® products, the instructions for use must be read carefully! If the instructions are not followed, the product will be excluded from the guarantee. Small, striking color or structure deviations, fluctuating material thicknesses and complaints after processing are also excluded from the guarantee.

The data sheet is based on development work and practical experience. The content does not indicate a contractual legal relationship. The processor / buyer is not released from the responsibility of testing our products for their suitability for the intended application. In addition, our general terms of business, delivery and payment apply. With the publication of a new edition of this data sheet, the previous information loses its validity as of 01/01/2020.