

| | | |
|-------------------------------------|------------------------|---|
| Product | Name | Organoid® WILDSPITZE GOLD |
| | Article number | WSP0000045GTARW |
| | Producer | Address ORGANOID® TECHNOLOGIES GMBH Nesselgarten 422 / Top 5 A-6500 Fließ Österreich |
| Description and applications | Name | Organoid® WILDSPITZE GOLD |
| | Description | Natural plant material in medium density on natural flax backing produced climate neutral in Tyrol |
| | Applications | As wallpaper As a compound in wood-working |
| Plant material and density | Plant material | Regional, hand-cut Alpine hay from the Tyrolean Alps |
| | Density | Medium density, backing material is part of the design |
| Size and weight | Size | Rolled goods, width 1 360 mm |
| | Thickness | 0,2 mm |
| | Weight | 250 g/m ² |
| Product requirements | Food-safety | Binding agent safe for usage in contact with food in accordance with EU-regulation 1935/2004 |
| Backing material | Material Properties | Golden paper (FSC-certified) Shimmering |
| Technical implementation | Cut | Use scissors, a cutter or a plotter |
| | Edges | Allow for imperfections 1-2 mm around the edges |
| | How to install | <u>As a compound in wood-working</u> -Process with normal wood-working machinery -Glue (e.g. white glue) is applied onto the wooden materials, as the fleece absorbs moisture and glue stains may appear on the front if glue is applied to the fleece -Cover the natural surface with the enclosed separating paper -Guidelines: Max. pressing temperature. 60°C Max. pressure 1 kg/cm ² Glue application: approx. 100 g/m ² Pressing time: approx. 15 minutes Pre-trials and tests are recommended |
| | Glue recommendations | As a compound in wood-working: |

White glue

Pay attention to

Surface must be clean, dry, weight-bearing, evenly absorbent, smooth, dust-free and neutral in colour. Recently plastered walls must be fully dried. Highly absorbent walls must be prepared with a suitable base.

For sensitive wood-working applications, use a counter-balance (enclosed on request). Symmetrical construction is recommended, which means using the same surface on the front and back side.

Acclimatisation of Organoid natural surfaces:

- Bring product to room temperature before unpacking
- Store product protected from light, at about 20°C and 30-60 % relative humidity.
- Storage:
 - Rolled goods: hanging system (e.g. paternoster)
 - Single panels: horizontal position (e.g. drawer system)

Processing guidelines available at:

<https://www.organoids.com/verarbeitung/>