

LAVENDEL medium - on Flax backing

Artikel Nr.

LAW0000060FVPRW

Use lavender to create a relaxing atmosphere in your interior spaces:

Lavender smells heavenly and is proven to reduce anxiety and stress. For this surface, we use lavender blossoms and a lefover product form lavender farming: fragrant stems of the plant are processed. This way, the surface noticably increases your wellbeing, while being environmentally friendly. The nicely natural flax backing is part of the design thanks to the medium density of the natural fibres.

- the fragrance of lavender is proven to reduce stress and anxiety
- tha natural flax backing is part of the design
- environmentally friendly use of leftovers

Fragrant lavender stems and blossoms in medium coverage on a natural Flax backing



Characteristics

Raw material	Fragrant lavender stems and blossoms
Scent	$\bullet \bullet \bigcirc$
Light fastness	$\bullet \bullet \bigcirc$
Abrasion resistance	$\bullet \circ \circ$
Vibrancy	$\bullet \bullet \bigcirc$

Technical details

Backing	Flax Backing	
Format	Rollenware, Breite: 1.360 mm	
MOQ	1 m² (ca. 0.74 running metre)	
Weight	480 g/m ²	
Thickness	1,2 mm	
Flexibility	bending radius up to 0.5 mm	
Translucency	light-permeable	

Material details

Wallpapering technique	Do not apply glue to the back of the wallpaper, but to the surface. Please note our glue recommendations.	
Overlap and double-cut	Each panel overlaps approx. 2 cm with the one next to it. Please note the edge tolerance.	
Free match	Free match The naturally scattered materials do not require matching patterns between panels.	$\rightarrow 0$
Breathable	The natural flax fleece backing is breathable, unbleached, ecological and climate regulating.	



Processing

Wallpaper

Installation of Organoid natural surfaces on Flax backing as a wallpaper:

- Wall-pasting technique
- Pay attention to Organoid glue recommendations
- Double cut: Each panel overlaps with the one next to it (approx. 2 cm)
- Cut with scissors, cutter or plotter
- Pre-trials recommended
- In the case of wallpapers, the effect is to be checked after processing three strips. Claims that go beyond the replacement of defective goods will not be accepted.

To Installation

wood workers

Installation of Organoid natural surfaces on Flax backing in woodworking:

- Process with normal wood-working machinery
- Glue (e.g. white glue) is applied onto the wooden materials, as the fleece absorbs moisture and glue stains may appear on the front if glue is applied to the fleece
- Cover the natural surface with the enclosed separating paper
- pressing temperature. 60°C
- For sensitive wood-working applications, use a counter-balance (enclosed on request)
- Cut with scissors, cutter or plotter
- Pre-trials recommended

To Installation



Inspiration





Organoid Technologies GmbH

6500 Fließ Nesselgarten 422 www.organoids.com info@organoids.com Tel. <u>+43 5449 200 01</u>

17.5.2024