

DATA SHEET

STRUCTURE-LINE OCEAN NA (SL)

SL OCEAN Anthracite AR SL OCEAN Aqua SL OCEAN Gold SL OCEAN Hollywood
SL OCEAN Iceblue AR SL OCEAN Rainbow SL OCEAN Silver SL OCEAN Hollywood Blue

Product information

Product	Produce
Characteristics	Thermoplastic synthetic material
Components	Polyethylen (PE, 50 µm) Decor: Polyethylene terephthalate (PET, 12-25 µm) Highly impact-resistant polystyrene (HIPS, 2 mm)
Shape/Condition	Solid state
Toxicology	No impairments known
Environmental hazards	No dangers known
Weight	2,12 kg/m ²
Material thickness Relief height	2 mm (± 0,1 mm) ca. 8 mm
Characteristics	Free from <ul style="list-style-type: none">• Plasticizers• Silicones

Fire behaviour

DIN 4102-1	Normally flammable	B2
------------	--------------------	----

Handling and storage

Storage recommendation	Horizontal, dry, protection from weather
Protective measurements	None

SIBU | DESIGN

STRUCTURE-LINE OCEAN NA (SL)

SL OCEAN Anthracite AR SL OCEAN Aqua SL OCEAN Gold SL OCEAN Hollywood
SL OCEAN Iceblue AR SL OCEAN Rainbow SL OCEAN Silver SL OCEAN Hollywood Blue

REACH information requirement

Classification according to REACH	Meets the current requirements of REACH and is not subject to labeling.
-----------------------------------	---

Transport

Transport	No dangerous good in the sense of the transport regulation
-----------	--

Other

Cleaning	Using warm diluted soapy water, without abrasive ingredients, if necessary with the help of a soft cloth or sponge. Household cleaners without solvents, which are suitable for plastic surfaces, are recommended as cleaning agents. Check the suitability of the cleaning agent on a hidden spot.
----------	---

Fault definition optical deviation	A defect is defined as one that is visible to the naked eye from a distance of 50 cm after 30 seconds in good lighting.
------------------------------------	---

Disposal	The material can be disposed of in household waste or taken to a suitable recycling or incineration plant in accordance with local regulations.
----------	---

Assembly	Due to the pattern, mechanical assembly (screws, spacers) is generally recommended. Applications in the ceiling area must be attached mechanically.
----------	---

Detailed information regarding our products can be found on our website at www.sibu.at.

The information in this data sheet is based on our experience and/or information from our suppliers. The data sheet was created to the best of our knowledge and with particular care. No liability can be assumed for misprints, standard errors and mistakes!

SIBU | DESIGN
Department Technology / Ternberg, 13.03.2024