

DATA SHEET

STRUCTURE-LINE OCEAN FLAME RETARDANT (FR) SA

SL OCEAN Anthracite AR FR
SL OCEAN Hollywood Blue FR

SL OCEAN Gold FR
SL OCEAN Iceblue AR FR

SL OCEAN Hollywood FR
SL OCEAN Silver FR

Product information

Product	Produce
Characteristics	Thermoplastic synthetic material
Components	Polyethylene (protective film, PE, 50 µm) Decor: polyethylene terephthalate (PET, 12-25 µm) Polyvinyl chloride hard (HPVC, 2 mm) Dispersion acrylic adhesive (adhesive, 0.11-0.23 mm) Cover silicone paper (0.08 mm)
Shape/Condition	Solid state
Toxicology	No impairments known
Environmental hazards	No dangers known
Weight	3.1 kg/m ²
Material thickness	2.2 mm (± 0.1 mm)
Characteristics	Free from silicone

Fire behavior

DIN EN 13501-1	Flame retardant	B – s2, d0
SIBU DESIGN STRUCTURE-LINE OCEAN FR products must be attached to substrates that have a fire protection classification A2 - s1, d0 according to EN 13501-1 (such as gypsum plasterboard or similar building materials) to achieve fire behavior of B - s2, d0 according to EN 13501-1.		

Handling and storage

Storage recommendation	Horizontal, dry, protection from weather
Protective measurements	None

SIBU | DESIGN

STRUCTURE-LINE OCEAN FLAME RETARDANT (FR) SA

SL OCEAN Anthracite AR FR
SL OCEAN Hollywood Blue FR

SL OCEAN Gold FR
SL OCEAN Iceblue AR FR

SL OCEAN Hollywood FR
SL OCEAN Silver FR

REACH information requirement

Classification according to REACH

Meets the current requirements of REACH and is not subject to labeling.

Transport

Transport

No dangerous good in the sense of the transport regulation (ADR).

Other

Cleaning

Using warm diluted soapy water, without abrasive ingredients, if necessary with the help of a soft cloth or sponge. Household cleaners without solvents, which are suitable for plastic surfaces, are recommended as cleaning agents. Check the suitability of the cleaning agent on a hidden spot.

Fault definition optical deviation

A defect is defined as one that is visible to the naked eye from a distance of 50 cm after 30 seconds in good lighting.

Disposal

The material can be disposed of in household waste or taken to a suitable recycling or incineration plant in accordance with local regulations.

The information in this data sheet is based on our experience and information from our suppliers. The data sheet was created to the best of our knowledge and with particular care. No liability can be assumed for misprints, standard errors and mistakes!

SIBU | DESIGN
Department of Technology / Ternberg, 20.08.2024